



ALLVAC Universal Recovery Unit

Universal High & Low Pressure Recovery



Combines capabilities of Evac Commercial & Lovac systems to offer great recovery rates on R11, R12, R22, R113, R123, R134a, R404, R500, R502, R410a & other high pressure refrigerants or blends. Rugged open drive compressor provides years of reliable service, even on refrigerants heavily contaminated with oil, air, moisture, & acids. Switching between refrigerants simply involves oil & filter changes along with evacuation of the unit. Air/water cooled option incorporates a water cooled plate exchanger in line with the air cooled condenser. This model may operate with or without condensing water.

| | |
|--------------------------------|------------------|
| Push/Pull Rates (R22) | 325-lbs/min |
| Vapor Rates (R22) | 6.0-lbs/min |
| Push/Pull Rates (R11) | 100-lbs/min |
| Vapor Rates (R11) | 0.66-lbs/min |
| Connections | 3/4" flare |
| Dimensions - Inches: l x w x h | 32" x 29" x 45" |
| Float Connection | 3-pin BH |
| Low Pressure Switch | 15" Hg or 29" Hg |

Included with purchase

| | |
|------------------------------------|---|
| One 48-cubic inch drier core | 50-ft power cord for controls |
| 12-ft tank float cable | 50-ft power cord for recovery unit |
| (2) 3/4"-5/8" & 5/8"-1/2" fittings | Two 3/4" x 10ft & One 3/4" x 20ft recovery hoses w/ ball valves |

Order number

| | | | | |
|----------------------|------------------------------|------------------------------|------------------|---------|
| ARH-A-230-3-E | 220-240V,50/60Hz,3Ph,3Hp,20A | Electromechanical Controls, | Air Cooled | 275 lbs |
| ARH-A-240-1-E | 220-240V,50/60Hz,1Ph,3Hp,30A | Electromechanical Controls, | Air Cooled | 275 lbs |
| ARH-A-460-3-E | 360-575V,50/60Hz,3Ph,3Hp,15A | Electromechanical Controls , | Air Cooled | 275 lbs |
| ARH-A-D24-1-E | 240/460V 50/60Hz,1PH,3Hp,30A | Electromechanical Controls, | Air Cooled | 285 lbs |
| ARH-W-230-3-E | 220-240V,50/60Hz,3Ph,3Hp,20A | Electromechanical Controls, | Air/Water Cooled | 290 lbs |
| ARH-W-240-1-E | 220-240V,50/60Hz,1Ph,3Hp,30A | Electromechanical Controls, | Air/Water Cooled | 290 lbs |
| ARH-W-460-3-E | 360-575V,50/60Hz,3Ph,3Hp,15A | Electromechanical Controls, | Air/Water Cooled | 290 lbs |
| ARH-W-D24-1-E | 240/460V,50/60Hz,1Ph,3Hp,30A | Electromechanical Controls, | Air/Water Cooled | 300 lbs |

Reftec International Systems, llc.
6950 112th Circle
Largo, Fl. 33773

Phone) 800-214-4883
Fax) 727-827-2882
Web) www.reftec.com