



RefTec
INTERNATIONAL SYSTEMS LLC



Lite Evac Cart Mount Recovery Unit

Portable High Speed Recovery of All High Pressure Refrigerants

SPECIFICATIONS

Push/Pull Rates (R22)	81-lbs/min
Vapor Rates (R22)	2.14-lbs/min
Push/Pull Rates (R134a)	76-lbs/min
Vapor Rates (R134a)	2.04-lbs/min
Push/Pull Rates (R410a)	65-lbs/min
Vapor Rates (R410a)	1.75-lbs/min
Dimensions (lwxh in inches)	38"x23"x24"
Float Connection	3-pin BH
Connections	1/2" flare
Low Pressure Switch	15" Hg
Liquid and Vapor ports:	1/2" threaded connect

Lite Evac Recovery Unit

High Speed, High Efficiency Recovery of all High Pressure Refrigerants

- **Fast and portable unit for high pressure refrigerants**
- **Unit is mounted in a solid lightweight aluminum frame**
- **For use with medium-large tonnage chillers**
- **2 large tires for ease of mobility**
- **R410a rated**
- **Lightweight commercial unit at only 161lbs**
- **80% tank full float switch and 12' cable**
- **Air cooled unit**
- **Heavy duty lift handles**
- **ETL certified**

Certifications Certified by ETL to UL-1963 standards

Rated in accordance with ARI Standard 740-1998

Order Number

Specifications

LRH-HT-A-115-E

115V/60HZ/1PH/20A,110V/50HZ/1PH/20A

LRH-HT-A-240-E

230V/60HZ/1PH/20A,220V/50HZ/1PH/20A

INCLUDED

2- 30cu. Inch Filter Driers

80% Tank Float Cable (12ft)

50ft. Power Cord

Optional Accessories

050-010-LRH Hose Kit consisting of (2) 10' and (1) 20' hoses, all 1/2" diameter

LRHWCK Water Cooled Condensing Kit with (2) 4' refrigerant hoses

www.reftec.com

800-214-4883