



VACUUM PUMP LOVAC

R11, R113, R123, R114, R245fa Recovery Unit With Welch 10.6 CFM Vacuum Pump

The Industries Fastest Certified Low Pressure Refrigerant Recovery Rates



- Transfers 134-lbs/min push pull
- 1.26-lbs/min vapor on R11.
- Water-cooled plate exchanger provides excellent condensing capacity.
- Easy Operations
- Evacuating lines and switching from liquid to vapor recovery modes simply involves turning three 3-way hand valves & rerouting one hose
- 10.6 CFM Vacuum Pump
- Pulls greater than 29Hg vacuum

Specifications

Push/Pull Rates (R11): 134-lbs/min
 Vapor Rates (R11): 1.26-lbs/min
 Connections: 3/4" flare or optional quick connects
 Dimensions - Inches: l x w x h : 30 x 18 x 35 (shipping 48 x 40 x 42)
 Weight: 225-lbs (shipping 300-lbs)
 Float Connection: 3-pin BH 29" Hg
 Certified by ETL to UL-1963 standards
 Rated in accordance Certifications with ARI Standard 740-1998

Included with purchase

One 48-cubic inch drier core	50-ft power cord
Two 3/4" x 10ft recovery hoses w/ ball valves	12-ft tank float cable
One 3/4" x 20ft recovery hose w/ ball valves	Two 3/4"-5/8" & 5/8"-1/2" fittings

Order number Power options Controls / cooling options

CRL-V-115-E	110-120V,50/60Hz,1Ph,1Hp,15A	Electromechanical , water cooled
CRL-V-240-E	220-240V,50/60Hz,1Ph,1Hp,15A	Electromechanical , water cooled
CRL-A-V-115-E	110-120V,50/60Hz,1Ph,1Hp,15A	Electromechanical , air cooled
CRL-A-V-240-E	220-240V,50/60Hz,1Ph,1Hp,15A	Electromechanical , air cooled

KIT001 Quick connect kit for Lovac unit & hoses



Quick connect kit (KIT001) may be purchased separately & installed to flare connections on Lovac & hoses.

Reftec International Systems, LLC.
 10530 Portal Crossing, Suite 101
 Bradenton, Fl. 34211

P) 800-214-4883
 F) 941-750-0222
 W) www.reftec.com