



# CHEETAH

R11, R113, R123, R114, R245fa Recovery Unit With Welch 10.6 CFM Vacuum Pump

## The Fastest Certified Low Pressure Refrigerant Recovery Rates



- R123: 123lbs/min push/pull: .91lbs/min vapor
- Water-cooled plate exchanger provides excellent condensing capacity
- Easy operations
- Simple switch from liquid to vapor recovery
- Built in hose evacuation setting
- Automatic low pressure cutoff
- Automatic high pressure safety cutoff
- 10.6 CFM heavy duty vacuum pump
- Pulls greater than 29Hg vacuum
- Upright cart mount for easy portability
- Large tires for rough terrain

### Specifications

Push/Pull Rates	R123- 123-lbs/min
Vapor Rates	R123- .91-lbs/min
Connections:	3/4" Male Flare or Optional Quick Connects
Dimensions - Inches:	l x w x h : 26 x 22 x 44
Weight:	228-lbs (shipping 300-lbs)
Float Connection:	3-pin BH 29" Hg
Condenser Connection:	Standard 3/4" Garden Hose Connection

Certified by ETL to UL-1963 standards  
 Rated in accordance Certifications with ARI Standard 740-1998

### Included with purchase

- Two 41 cubic inch filter driers
- Two 3/4" x 10ft recovery hoses w/ ball valves
- One 3/4" x 15ft recovery hose w/ ball valves
- 25-ft power cord
- 12-ft tank float cable

Order number	Power options	Cooling Options
CLP-115	103-127V,50/60Hz,1Ph,2Hp, 20A	Water Cooled
CLP-240	220-240V,50/60Hz,1Ph,2Hp, 20A	Water Cooled
KIT001	Quick connect kit for Lovac unit & hoses	



Quick connect kit (KIT001) may be purchased separately & installed to flare connections on Cheetah & hoses.

Reftec International Systems, LLC.  
 6950 112<sup>th</sup> Circle  
 Largo, FL 33773

P) 800-214-4883  
 F) 727-827-2882  
 W) www.reftec.com