

## Lovac/ASME Packaged Recovery Unit

R11 at 100lbs/minute push/pull, .66 lbs/minute vapor



### SPECIFICATIONS

Push/Pull Rates (R11)	100-lbs/min
Vapor Rates (R11)	.66-lbs/min
Float Connection	3-pin BH
Connections	3/4" flare
Low Pressure Switch	29" Hg
Liquid and Vapor ports:	3/4" threaded connect

### Lovac/ASME Tank Mount

High Speed, High Efficiency Recovery and storage of all Low Pressure Refrigerants

- Packaged recovery/storage unit for Low pressure refrigerants
- Unit is hard piped and permanently mounted on ASME tank
- For use with large tonnage chillers
- Capable of storing up to 7868lbs of R11 at 80% capacity
- Dual 250-psi relief valves on diverting valve
- Mounted on casters for mobility
- 80% tank full float switch and 12' cable
- Bottom drain connection
- Liquid and Vapor ports: 3/4" threaded connection with isolation ball valves
- ETL certified

Certifications Certified by ETL to UL-1963 standards  
 Rated in accordance with ARI Standard 740-1998

Order Number	Specifications	Tank/gal	Weight
CRL-115-A-250	103-127V,50/60Hz,1Ph,2Hp,20A	250	2050lbs
CRL-115-A-500	103-127V,50/60Hz,1Ph,2Hp,20A	500	2275lbs
CRL-115-A-850	103-127V,50/60Hz,1Ph,2Hp,20A	850	2875lbs
CRL-115-A-1000	103-127V,50/60Hz,1Ph,2Hp,20A	1000	3585lbs
CRL-240-A-250	220-240V,50/60Hz,1Ph,2Hp,15A	250	2050lbs
CRL-240-A-500	220-240V,50/60Hz,1Ph,2Hp,15A	500	2275lbs
CRL-240-A-850	220-240V,50/60Hz,1Ph,2Hp,15A	850	2875lbs
CRL-240-A-1000	220-240V,50/60Hz,1Ph,2Hp,15A	1000	3585lbs

#### INCLUDED

- One 48cu" filter core
- One 10' x 3/4" diameter hose
- Two 20' x 3/4" diameter hoses
- 100' power cord for controls
- 50' power cord for unit
- 12' tank float cable
- Two each 3/4"-5/8" and 5/8"-1/2" reducing fittings