



# HYPERWATT Water Heating Chiller Pressurizer

## Higher 30kW Capacity Rapidly Pressurizes a Chiller



Portable Service Cart Model

- Microprocessor displays step-by-step operating instructions.
- When desired chiller pressure level is reached, the pump shuts down. Automatically re-energizes to maintain stable pressure.
- Microprocessor monitors chiller pressure and prevents over-pressurization.
- Thermal sensors prevent heating element overload and burnout.
- Sensor halts operations should water flow cease.
- 100-lb portable model easily managed by one man and maneuvered around tight mechanical rooms.
- Permanent mount unit is hard piped to a chiller. Maintains the chiller at slightly positive pressure during seasonal shutdown.

### Specifications

Power: Controls & Water Pump  
Dimensions – Inches: l x w x h  
Weight  
Pressure settings

115/60/1 110/50/1  
20 x 22 x 51  
100-lbs  
0 to 10-psi

### Included with purchase

50-ft power cord for controls  
50-ft power cord for recovery unit  
20-ft x ¼” refrigerant hose  
Two 15-ft water hoses  
Two ¾” water swivel fittings

### Order Number

**HPS-C-D24-3**  
**HPS-P-D24-3**  
**HPS-C-575-3**  
**HPS-P-575-3**

### Voltage Options

220-480V,50/60Hz,3Ph,20/40A  
220-480V,50/60Hz,3Ph,20/40A  
575V,50/60Hz,3Ph, 20/40A  
575V,50/60Hz,3Ph, 20/40A

### Model

Service Cart  
Permanent Mount  
Service Cart  
Permanent Mount

RefTec International, Inc.  
10530 Portal Crossing W,  
Suite 104  
Bradenton, FL 34211

Tel: 800-214-4883  
fax: 941-750-0222  
[www.reftec.com](http://www.reftec.com)  
email: sales@reftec.com