




RefTec
INTERNATIONAL SYSTEMS LLC



Lite Evac Recovery Unit

Portable High Speed Recovery of All High Pressure Refrigerants

SPECIFICATIONS

Push/Pull Rates (R22)	81-lbs/min
Vapor Rates (R22)	2.14-lbs/min
Push/Pull Rates (R410a)	65-lbs/min
Vapor Rates (R410a)	1.75-lbs/min
Dimensions (l x w x h in inches)	30" x 21" x 22"
Float Connection	3-pin BH
Connections	1/2" flare
Low Pressure Switch	15" Hg
Liquid and Vapor ports:	1/2" threaded connect

Lite Evac Recovery Unit

High Speed, High Efficiency Recovery of all High Pressure Refrigerants

- **Fast and portable unit for high pressure refrigerants**
- **Unit is mounted in a solid lightweight aluminum frame**
- **For use with medium-large tonnage chillers**
- **4 Heavy duty casters for ease of mobility**
- **R410a rated**
- **Lightweight commercial unit at only 161lbs**
- **80% tank full float switch and 12' cable**
- **Air cooled unit**
- **Heavy duty lift handles**
- **ETL certified**

Certifications Certified by ETL to UL-1963 standards

Rated in accordance with ARI Standard 740-1998

Order Number	Specifications
LRH-115-E	115V/60HZ/1PH/20A, 110V/50HZ/1PH/20A
LRH-240-E	230V/60HZ/1PH/20A, 220V/50HZ/1PH/20A

INCLUDED

2- 30cu. Inch Filter Driers
80% Tank Float Cable (12ft)
50ft. Power Cord

Optional Accessories

050-010-LRH Hose Kit consisting of (2) 10' and (1) 20' hoses, all 1/2" diameter

www.reftec.com

800-214-4883