



# MITYVAC

## 2.0-hp Open Drive Recovery Unit



### Highest Recovery Speed of any 115V Recovery System

- Larger 2.0-hp open drive compressor, 1/2" lines, two point vapor extraction, & oversized air cooled condenser allow fast recovery of charges from chillers of 400-tons and larger.
- Services R12, R22, R500, R502, R134a, MP39, R409a, R507 and other high pressure refrigerants & blends.
- Purging hoses and switching from liquid to vapor recovery modes simply involves turning three 3-way hand valves - no switching of hoses is necessary.
- 450-psi high pressure shut off and 15-in. Hg vacuum low pressure shut off.

### Specifications

Certified by ETL to UL-1963 standards  
 Rated in accordance with ARI Standard  
 740-1998

Push/Pull (R22)	55-lb/min
Direct Liquid (R22)	N/a-lb/min
Vapor (R22)	1.56-lb/min
Weight:	100-lbs (45.5kg)
Motor	2.0 Hp
Connections	1/2-in. Flare
Dims. Inches: l x w x h	19 x 14 x 21
Float Connection	3-pin BH
Low Pressure Switch	15" Hg

### Order Information

**MRH-115-E** 103-127V,50/60Hz,1Ph,2.0Hp,20A

**MRH-240-E** 220-240V,50/60Hz,1Ph,2.0Hp,15A

- Included:
- Two 30 cubic inch filter driers
  - 12-ft float cable, 3 pin (FVC-012)
  - Two 1/2" flare swivels
  - Power cord adapter (overseas only)
  - Requires 4 hoses sold separately

RefTec International, Inc. 10530  
 Portal Crossing W, Suite 104  
 Bradenton, FL 34211

Tel: 800-214-4883  
 Sales fax: 941-750-0222  
[www.reftec.com](http://www.reftec.com)  
 email: sales@reftec.com